



Color Variants

RF471304
fully integrated
Niche width 76.2 cm, Niche height 213.4 cm

Included accessories

1 x ice cube scoop.
1 x connection set.
1 x Ice storage container.
large.

Optional accessories

RA450010
Activated charcoal filter for water filter system including saturation indicator

Installation Accessories

RA421710
RA425110
Handle bar, stainless steel, long
RA460020
Connecting element for vertically split appliance fronts (for a flush front)

RF471304

Vario freezer 400 series

fully integrated

Niche width 76.2 cm, Niche height 213.4 cm

Stainless steel interior with solid anthracite aluminium elements
Warm white and glare-free LED light spots
Opening assist for door with two options:
1. Push-to-open function for integration into handleless furniture front
2. Pull-to-open function to facilitate opening the door using a handle
The drawers in the RC and RF models are positioned at the same height. With side-by-side installation, the glass shelves and door racks can be aligned on the same level
Material and aesthetics of interior as for RC model
- Glass shelves
- Solid anthracite aluminium door racks
Flat stainless steel inner door, full-length
Almost invisible rail system for shelves and door racks for flexible positioning
Integrated ice maker with fixed inlet water connection
TFT touch display
Net volume 429 litres

Handling

TFT touch display operation.
Clear text display.

Features

Dynamic cold air distribution.
Automatic defrosting with defrost water evaporation.
Rest mode certified by Star-K.
When rest mode is active, the appliance can only be opened using a handle.
Open-door and malfunction alarm.
Integrated WiFi module for digital services (Home Connect).
The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: www.home-connect.com

Freezing

No-frost technology with fast freezing at -30 °C.
Temperature adjustable from -16 °C to -24 °C.
4-star freezer compartment.
Freezing capacity 20 kg/24 h.
Storage time after a malfunction 14 h.
4 safety glass shelves, white glass, 3 of which are individually height adjustable.
2 fully extendable drawers with transparent front.
Brilliant LED light spots with warm white, glare-free light.
Flat door rail system with fully flexible positioning of door racks.
4 height-adjustable door racks.

Ice maker

Integrated in the freezer compartment, with fixed inlet water connection.
Particle filter for water inlet, integrated in ventilation grille area.
Can be switched off.
Ice cube production approx. 1.7 kg/24 h.

Characteristics

Thermometer freeze section
Light
Yes
Product category
Upright freezer
Construction type
Built-in
Door panel options
Not possible
Frost free system
Fridge and freezer
Height of the product (mm)
2125
Width of the product (mm)
756
Depth of the product
608
Required niche size for installation (HxWxD)
2134.0 x 762.0 x 610
Dimensions of the packed product (HxWxD) (mm)
2270 x 770 x 850
Net weight (kg)
178.454
Gross weight (kg)
195.0
Connection rating (W)
300
Current (A)
3
Frequency (Hz)
50-60
Approval certificates
CE, VDE
Length of electrical supply cord (cm)
300
Energy efficiency class
Energy consumption (kWh)
Total annual energy consumption (kWh)
Freezing capacity (kg)
Door hinge
Left reversible
Storage Period in Event of Power Failure (h)
14
Color / Material body
Defrost process
Warning signal / malfunction
Audible
Lockable door
No
Number of drawers/baskets (Stck)
2
Number of freezing flaps (Stck)
0
EAN code
4242006262204

Consumption and connection features
Brand
Gaggenau
Product name / Commercial code
RF471304
Product category
Upright freezer
Energy efficiency class (2010/30/EC)
A++
Energy consumption annual (kWh/annum) - NEW (2010/30/EC)
340.00
Freezer Net capacity (l) - NEW (2010/30/EC)
429
Frost free system
Fridge and freezer
Temperature rise time (h)
14
Freezing capacity (kg/24h) - NEW (2010/30/EC)
20
Climate class
SN-T
Noise level (dB(A) re 1 pW)
42
Installation type
N/A

created on 2018-12-05
Page 1

Removable ice storage container with approx. 4 kg capacity.

Product rating

Energy efficiency class A++ at a range of energy efficiency classes from A++ to D.
Energy consumption 340 kWh/year.
Noise level 42 dB (re 1 pW).

Planning notes



Flat hinge.
Door opening angle of 115°, fixable at 90°.
For installation with a door opening angle of 90° the ice storage container must be exchanged for the small ice storage container (RA 448220). This must be done prior to fixing the door.
Max. door panel weight 25 kg.
Shut-off valve for water connection must be planned next to the appliance and always be accessible.
If the water pressure exceeds 0.8 MPa (8 bar), connect pressure relief valve between water tap and hose set.

Connection


Total connected load 0.300 kW.
Connecting cable 3.0 m, pluggable.
Water inlet.
Supply hose 2.0 m with 3/4" connection.
Water pressure 2.4 to 8.3 bar.
Door hinge left, reversible.

RF471304
 Vario freezer 400 series
 fully integrated
 Niche width 76.2 cm, Niche height 213.4 cm

created on 2018-12-05
 Page 2




Wall clearance RB 472/RC/RF/RW



Recess width C	D	E1	E2
457 mm	525 mm	235 mm	265 mm
610 mm	677 mm	299 mm	330 mm
762 mm	830 mm	364 mm	395 mm
914 mm	980 mm	428 mm	460 mm

In the drawing, a unit front thickness of 19 mm and a Gaggenau unit handle of 49 mm were taken as a basis.

Base detail



Based on the standard appliance height, the height of the plinth is 102 mm. Maximum plinth thickness 19 mm.